




# REKOLA

## Rekola Reflex AquaPlus



Product code	Color code	Dimension	
10-0057	grey	57 x 18 cm	<b>Rekola Reflex</b> fringe mop with 17 lanes Polyester yarn 150D*x 30= 4500 D, tufted loops on Polyester/Cotton 70/30% canvas Multiple use 195 grs 4 Color tagged.
<b>Packed</b>	5 pcs pp bag 		20 pcs 5-pack per transport box
<b>Where:</b>	All smooth and sealed hard top floorings for cleaning results: e.g. school, university, office, public building, hospitality, residential areas. Especially for dusting, waxing and entrance cleaning at winter circumstances.		
<b>How:</b>	In conjunction with <b>Rekola Reflex</b> 50 cm squeegee and <b>Rekola Reflex</b> 100/180 extendable handle As preparation on a cleaning trolley <b>charge cloths in a closed container</b> like a. 14 Ltr. rectangle box with lid. Put the cloths inside and pour equally the terminated fluid over the cloths, leave for a while with closed lid. <b>Alternatively charge cloths in a washing machine</b> , by adapting the spinning of the last rinse. <b>Avoid</b> overdosing, bleach and softeners		
<b>Charge:</b>	With clean water; optional diluted with for Polyester suitable chemical according supplier instruction. <i>Please be aware that some chemicals may cause damage to user, material and environment</i> Depending on floor circumstances charge the cloths with 300-500 ml per cloth; <b>Regardless the charging liquid: avoid overdosing</b>		

# REKOLA

Maintenance	
<b>Laundry:</b>	
<b>Washing:</b>	<p>rinse twice assuring all cleaning chemicals are removed</p> <p>main program for synthetic fibers at 95°C, for environmental reasons at 60° C or less is preferred</p> <p>rinse twice assuring all laundry agents are removed</p> <p>temperatures and water volume according</p>
	tumble drying at lower heat
	avoid use of bleach and or softener
	low water level during processing or overloading washing machine (max a. 80% of door window) may cause irreversible damage to cloths.
<b>Disinfection:</b>	non –bleach disinfectant* laundry agent and autoclaving may be used if required *e.g. peroxide based; this may affect colors
<b>Durability:</b>	500 washing cycles. Rough surfaces like safety flooring will reduce lifetime expectations
<b>Disposable:</b>	Rekola Reflex AquaPlus mops are purely synthetics: may be used for recycling programs; or because of their high energy value and with no other than CO <sub>2</sub> and water as emission, safely disposed by controlled energy-supply programs.
Components	
<b>Body:</b>	<b>100% PES loops</b> 150*30= 4500 D tufted on 80/20% Polyester/Cotton canvas
<b>Borders:</b>	<b>100% PES</b>
Characteristics	
<b>Shrinkage:</b>	< 6% at recommended washing instructions
<b>Non-Touch</b>	In conjunction with Rekola Reflex squeegee tool, dirty cloths are not touched when demounting.
<b>Patent:</b>	FI2010000028 Floor Maintenance Device and Cloth
Guarantee	
<p>500 times use and wash in general hygiene cleaning circumstances at a maintained non-safety sealed floor.</p> <p>More usages can be achieved if considering optimal laundry and cleaning conditions. For instruction and details ask your distributor.</p>	