

REKOLA

REFLEX H MOPCLOTH 100% UMF

Make a difference with REFLEX:



Outstanding Performance & Versatility:

Deep Cleaning, Multifunctional and Ergonomical Up to 50 sqm more per mopcloth



Climate & Eco friendly:


Less water and chemicals. Residue Free Cleaning




Improves cleaning economy:



Saves time and space and cut total costs



Product code	Color code	Dimension	
18 - 2055	green	54 x 22,5 cm	REFLEX H MOPCLOTH 100% UMF , Multiple use, 88 grs/pcs
Package:	5 pcs pp bag  32 pcs 5-pack per transport box		



Application areas:	The REFLEX 2-in-1 cleaning system is designed for all types of smooth and sealed hard top floorings. Main application areas:		
	 Healthcare sector	 Public Areas & General Buildings	 Food Industry & HoReCa

How to use the system:	REFLEX H MOPCLOTH is double sided and is used in conjunction with REFLEX POWER SQUEEGEE 50 cm and REFLEX EXTENDABLE HANDLE 100/180 cm.
	<p>CHARGING: REFLEX H MOPCLOTH can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.</p> <p>CHARGING H MOPCLOTHS ON THE TROLLEY: 1. Put H MOPCLOTHS in a container, e.g. 6 Ltr. Rectangle bucket or box with lid. 2. Pour the desired fluid equally over the cloths inside the container. 3. Leave for a while with closed lid. Ready to clean!</p> <p>ABOUT DOSING: Avoid overdosing regardless the charging liquid. Some chemicals may cause damage to user material and or environment. Depending on floor circumstances, charge the H MOPCLOTH with 60-120 ml per MOPCLOTH.</p>

Eco Labeled:	 	<p>Rekola support Residue Free Cleaning. Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health REFLEX H MOPCLOTHS are designed to reduce and remove residue that resist traditional cleaning methods. For more information please contact Rekola</p>
	3083 0027	

REKOLA

Maintenance

Laundry: 	<p>Rinse twice cold to ensure all cleaning chemicals are removed. Main program for synthetic fibers at 60°C or less is preferred. Rinse twice after ensuring all laundry agents are removed.</p> <p>Adjust temperatures and water volumes accordingly.</p> <p>Machine drums can be filled with MOPCLOTHS up to 80% load (According Weber & Leucht laundry test DIN EN ISO 6330)</p> <p>In case of drying use tumble drying at 60°C or less.</p> <p>Do not use bleach or softener.</p> <p>Low water level during processing or overloading washing machine (max 80% of door window) may cause irreversible damage to cloths.</p>
Disinfection:	<p>Non-bleach disinfectant* laundry agent and autoclaving may be used if required *e.g. peroxide based; this may affect colors.</p>
Durability: 	<p>500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough surfaces like safety flooring may influence reduce lifetime expectations.</p>

Components

Body:	100% split Ultra Microfiber, 80% PES 20 PA and F= 0,154 Dtex.
Borders:	Overlock 100% PES. Sliding strip TPU and PES Mesh

Characteristics

Shrinkage:	SGS tested < 6% at recommended washing instructions. This can cause slight deformation, this does not affect the functionality.				
Color fastness	4-5.		<i>standard request</i> ≥ 3-4		
Charging	3,7 DAC value.		<i>standard request minimum</i> 2,5		
Abrasion	6,8 Gloss differential.		<i>standard request</i> < 20		
Weber & Leucht S301/1.3 dirt removal	Ceramic Tile SF 11	Dust A23	Damp	100%	<i>standard request</i> ≥ 70
	PVC- Flooring PL-03	Dust A23	Damp	95%	<i>standard request</i> ≥ 70
	Ceramic Tile SF 11	Muddy dirt A05	Damp	100%	<i>standard request</i> ≥ 70
	PVC- Flooring PL-03	Muddy dirt A05	Damp	100%	<i>standard request</i> ≥ 70
Bacteria reduction	E-coli 99,9% log >5,34 S. Aureus 99,85 log 2,82				
Non-Touch	In conjunction with REFLEX POWER SQUEEGEE, dirty cloths are not touched when demounting.				
Patent:	FI2010000028 Floor Maintenance Device and Cloth.				
Disposing:	REFLEX H MOPCLOTHS are purely synthetic: may be used for recycling programs; or because of their high energy value and with no emissions other than CO ₂ and water can be safely disposed by controlled energy-supply programs.				



Guarantee

500 times use and laundries according producers guidelines at 60°C, under general hygiene cleaning circumstances, at a maintained non-safety sealed floor.

Extended usage can be achieved if optimal laundry and cleaning conditions are considered.

For instruction and details ask your distributor.