

REKOLA

REFLEX S MOPCLOTH 50% UMF 50% PET

Make a difference with REFLEX:



Outstanding Performance & Versatility:

Deep Cleaning, Multifunctional and Ergonomical Up to 50 sqm more per mopcloth



Climate & Eco friendly:


Less water and chemicals. Residue Free Cleaning



Improves cleaning economy:

Saves time and space and cut total costs



| Product code | Color code | Dimension | |
|--|------------|--------------|--|
| 18-7050 | Grey | 54 x 22,5 cm | REFLEX S MOPCLOTH 50% UMF , Multiple use, 115 grs/pcs |
| Package: 5 pcs pp bag  20 pcs 5-pack per transport box | | | |

Application areas:

The REFLEX 2-in-1 cleaning system is designed for all types of smooth and sealed hard top floorings. Main application areas:



Healthcare sector



Public Areas & General Buildings



Food Industry & HoReCa

How to use the system:



REFLEX S MOPCLOTH is double sided and is used in conjunction with REFLEX POWER SQUEEGEE 50 cm and REFLEX EXTENDABLE HANDLE 100/180 cm.

CHARGING:

REFLEX S MOPCLOTH can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.

CHARGING S MOPCLOTHS ON THE TROLLEY:

1. Put S MOPCLOTHS in a container, e.g. 6 Ltr. Rectangle bucket or box with lid.
2. Pour the desired fluid equally over the cloths inside the container.
3. Leave for a while with closed lid. Ready to clean!

ABOUT DOSING:

Avoid overdosing regardless the charging liquid.

Some chemicals may cause damage to user material and or environment.

Depending on floor circumstances, charge the S MOPCLOTH with 60-120 ml per MOPCLOTH.

Eco Labeled:






3083
0027



Rekola support Residue Free Cleaning.

Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health REFLEX H MOPCLOTHS are designed to reduce and remove residue that resist traditional cleaning methods. For more information please contact Rekola

REKOLA

| Maintenance | |
|--|--|
| Laundry:  | Rinse twice cold to ensure all cleaning chemicals are removed. Main program for synthetic fibers at 60°C or less is preferred. Rinse twice after ensuring all laundry agents are removed. Adjust temperatures and water volumes accordingly. Machine drums can be filled with MOPCLOTHS up to 80% load (According Weber & Leucht laundry test DIN EN ISO 6330) In case of drying use tumble drying at 60°C or less. Do not use bleach or softener. Low water level during processing or overloading washing machine (max 80% of door window) may cause irreversible damage to cloths. |
| Disinfection: | Non-bleach disinfectant* laundry agent and autoclaving may be used if required *e.g. peroxide based; this may affect colors. |
| Durability:  | 500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough surfaces like safety flooring may influence reduce lifetime expectations. |
| Components | |
| Body: | 50% split Ultra Microfiber 80% PES 20 PA F= 0,154 Dtex, mixed with 50% PET. |
| Borders: | Overlock 100% PES . Sliding strip TPU and PES Mesh |
| Characteristics | |
| Shrinkage: | SGS tested <6% at recommended washing instructions. This can cause slight deformation, this does not affect the functionality. |
| Color fastness | 4-5. <i>standard request ≥ 3-4</i> |
| Charging | 4,2 DAC value. <i>standard request minimum 2,5</i> |
| Abrasion | The abrasion generated during use, is not advised for usage on softer material surfaces |
| Weber & Leucht S301/1.3 dirt removal | Ceramic Tile SF 11 Dust A23 Damp 93% <i>standard request ≥ 70</i> |
| | PVC- Flooring PL-03 Dust A23 Damp 87% <i>standard request ≥ 70</i> |
| | Ceramic Tile SF 11 Muddy dirt A05 Damp 100% <i>standard request ≥ 70</i> |
| | PVC- Flooring PL-03 Muddy dirt A05 Damp 100% <i>standard request ≥ 70</i> |
| Bacteria reduction | E-coli 99,89% log >2,96 S. Aureus 99,31 log 2,16  |
| Non-Touch | In conjunction with REFLEX POWER SQUEEGEE, dirty cloths are not touched when demounting. |
| Patent: | FI2010000028 Floor Maintenance Device and Cloth. |
| Disposing: | REFLEX S MOPCLOTHS are purely synthetic: may be used for recycling programs; or because of their high energy value and with no emissions other than CO ₂ and water can be safely disposed by controlled energy-supply programs. |
| Guarantee | |
| 500 times use and laundries according producers guidelines at 60°C, under general hygiene cleaning circumstances, at a maintained non-safety sealed floor. Extended usage can be achieved if optimal laundry and cleaning conditions are considered. For instruction and details ask your distributor. | |